



TRUCK OF THE FUTURE

DESIGNED TO FAST TRACK YOUR BUSINESS GROWTH



F F U U T T U U R R E E
F F U U T T U U R R E E

TATA MOTORS

ULTRA
TRUCKS | BUSES BEYOND TOMORROW

F F U F U T T U U R R E E



CHANGING NEEDS OF CUSTOMERS

CHANGING TECHNOLOGY

ULTRA
TRUCKS | BUSES | BEYOND TOMORROW

Keeping step with changes in these two spheres is what gives

Tata Motors the pioneering edge and leadership position in India's


commercial vehicles industry. The Tata Ultra ILCV Range is the

latest addition to the long list of 'firsts' from Tata Motors.

Designed for superior earning potential during their lifetime

through a higher performance promise to our customers, Ultra

ILCV trucks are a symbol of future trucking in India.



F F U F U T T U U

GEARED TO MEET **GROWING NEEDS**



GVW

Option of 8 T and 9.6 T

Load Body

Choose from Load Body lengths of 14, 17 and 20 ft

Load Margins

Gives you the advantage of higher load margin

Gearbox


An efficient Next Generation Gearbox enables a 'powered' performance

Clutch

A bigger and longer lasting clutch

Exterior

An idea-based exterior design for the sleek, futuristic looks



14, 17 & 20 FT




FUTURE

SMART FEATURES

World Class Cabin

- All-new steel cabin - aesthetically designed with elegant looks
- Hydraulic 45 deg tiltable cabin - easier engine access, lesser downtime, easier maintenance
- Dash-mounted gear lever - makes it walk through
- Passes pendulum test - reinstates safety
- Provision for AC
- Utility pockets on the head box - provides more storage space



Chassis


- Strongest chassis in its class with bolted design for increased modularity
- Rolled frame (Domex 650 high strength steel with high tensile strength)
- Straight long member - multiple wheelbase options

ULTRA
TRUCKS | BUSES BEYOND TOMORROW

Battery with Magic Eye

The Magic Eye indicates the state of charge of the battery & its electrolyte level as:

- If a green circle is viewed from the top of the Magic Eye - battery is fully charged
- If clear & transparent is viewed from the top of the Magic Eye - battery needs charging
- If red circle is viewed from the top of the Magic Eye - battery needs topping up



Brakes

- Front disc & rear drum - first time in an Indian commercial vehicle
- Better heat dissipation & better braking efficiency at high speed & loads
- Dual air over hydraulic - low weight
- Reduced braking effort
- Fail-safe circuit for safety




Steering

- Power steering with drooping characteristic
 - stability at high speed
- Tilt, telescopic & collapsible - suitable for any driver
- Low steering effort

ULTRA
TRUCKS | BUSES | BEYOND TOMORROW


Comfortable Seating

- Wider comfortable seats for 3 (driver + 2 passengers)
- Height adjustable driver seat
- Integrated headrests and armrest in centre
- Reduces driver fatigue
- Increases overall driving comfort



Lamps

- Head lamp - new generation stylised clear lens lamps
- Tail lamp - integrated with LED lamps, first time in a commercial vehicle



Instrument Cluster

- New generation multi-display electronic cluster
- Displays trip kmpl Indicators - fuel, water in fuel, low air pressure, rpm, speed, brake, seat belt, temperature, economy, assistance, time, neutral position, etc.
- Reliable combination switch

Suspension

- Front - parabolic leaf for smooth rides and comfort at variable loads
- Rear - semi-elliptical leaf spring
- Tuned shock absorbers - adjustable to GVW
- Both front and rear suspension come with rubber bush - no hassles of greasing now



F F U U T T U U R R E E

Tyres

- Radial tyres with low aspect ratio
- Better torque on wheel
- 55% longer life
- Less rolling resistance - better fuel economy



Convenient footsteps

- Easy to enter/exit for both driver & co-driver
- Stylish looks in sync with body design curves & arches

ULTRA
TRUCKS | BUSES BEYOND TOMORROW

Single Key Operation

For the comfort and ease of driver






Ultra 912



Ultra 812



Description	Ultra 912			Ultra 812		
Engine	TATA 497 TCIC					
Power	125 PS @2400 rpm					
Torque	400 Nm @ 1300-1500 rpm					
Clutch Type	Single Plate Dry Friction Type Booster Assisted, 330 mm					
Gearbox	GB 550 (6 Forward + 1 Reverse)					
Tyres	235/75R 17.5			225/75R 17.5		
Steering Type	Power Steering - Tilting & Telescopic					
Brakes	Front - Disc, Rear - Drum, Dual Air over Hydraulic					
Min. Ground Clearance (mm)	189			185		
Gradeability	33%			36%		
Fuel Tank Capacity (ltrs)	120 (33 & 39 WB) & 160 (45 WB)					
GVW (kg)	9600			8000		
Wheelbase (mm)	3310	3920	4530	3310	3920	4530
Turning Circle Diameter (mt)	10.8	12.9	15.2	10.8	12.9	15.2
	Cab, CLB, HD			Cab, CLB, HD		
Length (ft)	14	17	20	14	17	20
Width (ft)	7.4	7.4	7.4	7.4	7.4	7.4
Height (ft)	2.9, 6.7	2.9, 6.7	2.9, 6.7	2.9, 6.7	2.9, 6.7	2.9, 6.7
Warranty	3 years / 3 lakh km, whichever is earlier					
Colours	 White	 Blue	 Sardinia Red	 Yellow		



TATA MOTORS *Certified*
PRE-OWNED COMMERCIAL VEHICLES

Write to us: tataok@tatamotors.com
SMS: 5616161

TATA
Delight

Har Kadam Par Khushiyan

Enroll Today!
Write to us: delight@tatamotors.com or
Visit us at: www.tatadelight.com

SAMPOORNA
SEVA

(Annual Maintenance Contract Facility)

To avail Sampoorna Seva
at affordable price for your vehicle,
Call us on: 1800-258-2589 (Toll-free)
Write to us: amccustomer@tatamotors.com

Call us on: 1800-209-7979 (Toll-free)

TATA MOTORS

For more information on Ultra LCVs & ICVs, please visit our website: www.tatamotors.com. You can also contact our Sales Office:
Tata Motors Limited, 20th Floor, Tower 2, One Indiabulls Centre, 841 Senapati Bapat Marg, Mumbai 400 013. Tel.: +91 22 66586000;
Fax: +91 22 66586010

The illustrations and photographs may show accessories and items of optional equipment which are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrades without prior notice, in accordance with the Company's policy of continuous improvement. **Terms & Conditions apply.*